

MAIN DIMENSIONS AND WEIGHTS

	TYPE 710 M	TYPE 710 K
WHEEL BASE	2200 mm (86, 6 in.)	2200 mm (86, 6 in.)
TREAD FRONT	1440 mm (56, 6 in.)	1440 mm (56, 6 in.)
TREAD REAR	1440 mm (56, 6 in.)	1440 mm (56, 6 in.)
OVERALL LENGTH	4175 mm (164, 36 in.)	4175 mm (164, 36 in.)
OVERALL WIDTH	1760 mm (69, 29 in.)	1760 mm (69, 29 in.)
OVERALL HEIGHT (unloaded)	2045 mm (80, 51 in.)	2045 mm (80, 51 in.)
HEIGHT OF PLATFORM (loaded)	930 mm (36, 6 in.)	930 mm (36, 6 in.)
LENGTH OF LOADING AREA	2250 mm (88, 58 in.)	2250 mm (88, 58 in.)
WIDTH OF LOADING AREA	1590 mm (62, 59 in.)	1590 mm (62, 59 in.)
LOADING AREA	3, 5 m ² (37, 66 sq. ft)	3, 5 m ² (37, 66 sq. ft.)
GROUND CLEARANCE (below the axle drive housing; loaded)	335 mm (13, 18 in.)	335 mm (13, 18 in.)
FORDING DEPTH	600 mm (23, 62 in.)	600 mm (23, 62 in.)
DRY WEIGHT	1960 kg (4321 lb.)	2030 kg (4476 lb.)
PAY LOAD	1090 kg (2403 lb.)	1070 kg (2359 lb.)
PERMISSIBLE AXLE LOAD FRONT	1550 kg (3417 lb.)	1550 kg (3417 lb.)
PERMISSIBLE AXLE LOAD REAR	1550 kg (3417 lb.)	1550 kg (3417 lb.)
TOTAL PERMISSIBLE WEIGHT	3050 kg (6725 lb.)	3100 kg (6835 lb.)
TRAILER - without brake	750 kg (1653, 7 lb.)	750 kg (1653, 7 lb.)
- with overrunning brake	depending on the type of the trailer coupling up to 5000 kg (11013 lb.)	

CAPACITY AND VISCOSITY

FUEL TANK	75 l (16, 5 imp. gal.) ; With type 710 M 125 l (27, 5 imp. gal.) if required
ENGINE <i>Isoto</i>	7 l (1, 5 imp. gal.) HD engine oil summer SAE 30, winter SAE 10 (specification MIL-L-2104 B)
<i>Wechselgetriebe</i> CHANGE SPEED GEARBOX	2 l (0, 44 imp. gal.) transmission oil
<i>Gruppengetriebe</i> REDUCTION GEAR	* SAE 80 (specification MIL-L-2105)
<i>Achsantrieb</i> AXLE DRIVE	2, 3 l (0, 50 imp. gal.) transmission oil SAE 80 (specification MIL-L-2105)
<i>Radantrieb links</i> WHEEL DRIVE REAR	2 l (0, 44 imp. gal.) transmission oil (specification MIL-L-2105)
<i>Radantrieb vorne</i> WHEEL DRIVE FRONT	0, 35 l (21, 3 cu. in.) for each wheel drive transmission oil SAE 80 (specification MIL-L-2105)
	0, 4 l (24, 4 cu. in.) for each wheel drive transmission oil SAE 80 (specification MIL-L-2105)

* GX 015 80