

STEERING	<i>lenkany</i>	0,45 l (27,4 cu.in.) transmission oil SAE 80 (specification MIL-L-2105)
BRAKE	<i>brusac</i>	0,5 l (30,5 cu.in.) brake fluid (specification SAE J 1703)
CLUTCH	<i>Kupplany</i>	0,2 l (12,2 cu.in.) brake fluid (specification SAE J 1703)
LOCKS	<i>Sperer</i>	0,4 l (24,4 cu.in.) brake fluid (specification SAE J 1703)

FUEL CONSUMPTION

ROAD OPERATION (DIN 70030)	18 l / 100 km (15,7 miles / imp.gal.)
CROSS COUNTRY	6 - 10 l / h (1,3 - 2 imp.gal./h)

PERFORMANCES

TOP SPEED	100 km / h (62,15 mph)
MINIMUM SPEED	4 km / h (2,5 mph)
MAXIMUM HILL CLIMBING	On dry ground up to the adhesive limit

BULB TABLE

VEHICLE LIGHTENING	
HEAD LIGHT	2 each twin filament bulbs 24 V 55/50 W
CAMOUFLAGED HEAD LAMP	1 each 24 V 21 W
PARKING LIGHT	2 each 24 V 4 W
FRONT BLINKER	2 each 24 V 21 W
REAR LIGHT	2 each 24 V 5 W
REAR BLINKER	2 each 24 V 21 W
STOP LIGHT	2 each 24 V 21 W
NUMBER PLATE LIGHT	2 each 24 V 2 W
READ LIGHT	1 each 24 V 4 W
INTERNAL LIGHTING	2 each 24 V 5 W
SPEEDOMETER LIGHT	1 each 24 V 2 W
FUEL GAUGE LIGHT	1 each 24 V 2 W

CONTROL LIGHTS

OIL PRESSURE INDICATION	1 each 24 V 2 W
HAND BRAKE AND HYDRAULIC BRAKE CONTROL	1 each 24 V 2 W
CHARGING CURRENT	1 each 24 V 2 W
HEADLIGHT BEAM	1 each 24 V 2 W
BLINKER	1 each 24 V 2 W
ENGINE SPEED WARNING LIGHT	1 each 24 V 2 W
INDICATING LIGHT FOR HANDLAMP	1 each 24 V 2 W